

UNITED ALLINONE TRACTOR OIL

United Allinone Tractor Oil is specially designed to meet all the necessary lubrication requirements found in any part of a modern tractor, such as engine, transmission, hydraulic system and wet brake.

Incorporated with both the latest S.T.O.U. technology and U.T.T.O technology, United Allinone Tractor Oil is available in different SAE multi-grades, and therefore can be used under all weather and seasons conditions. Furthermore, the “Only one oil for all parts lubricant” also can significantly reduce the inventory cost and eliminate the chances of using the “wrong oil”.

APPLICATIONS / BENEFITS

- High engine performance.
- Only one oil for all parts lubrication.
- Extended service life.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
SAE Viscosity Grade	SAE J 300	5W30	10W30	15W40	15W50
Specific Gravity @ 15 °C	ASTM D 4052	0.875	0.886	0.890	0.891
Flash Point, °C	ASTM D 92	202	204	210	220
Pour Point , °C	ASTM D 97	-36	-27	-24	-18
Kinematic Viscosity @40°C (cSt)	ASTM D 445	64.7	71.3	103.7	128
@100°C (cSt)	ASTM D 445	11.1	11.20	14.32	14.42
Viscosity Index	ASTM D 2270	165	149	141	144
TBN, (mgKOH/g)	ASTM D 2896	10.9	10.9	10.9	10.9
Color	ASTM D 1500	<4.5	<4.5	<4.5	<4.5

MEETS THE REQUIREMENTS OF

- API CG-4
- API CF-4, CF, CE/SF, CD/SF
- API CD/SE
- API GL-4
- ACEA E3
- Allison C-4
- Caterpillar T0-2
- CNH MAT 3525, 3526
- Ford M2C134D
- Ford M2C86B, C
- Ford New Holland 82009201, 2, 3
- Ford: M2C159B, C
- Hydrostatic Trans Fluid
- J.I Case/Case Int: MS-1204,6,7,9
- John Deere J20C, J20D
- John Deere: J27
- Massey Ferguson: M1135
- Massey Ferguson: M1139
- Massey Ferguson: M1144
- Massey Ferguson: M1145
- Massey Ferguson: M1145
- MB 227.1
- MB 228.1 (in part synthetic)
- Sauer Sunstrand/ Danfoss:
- Sperry Vickers/ Eaton: I-280-S
- Sperry Vickers/ Eaton: M2950S
- Trans Massey Ferguson: M1143
- ZF TE-ML 06A
- ZF TE-ML 06B (inc. 06R), 06C, 07B