

UNITED GAS ENGINE OIL

United Ash Gas Engine Oil is a premium high performance SAE 40 gas engine oil that is formulated from select high quality, hydrotreated base stocks and an advanced technology additive system engineered to provide excellent protection. It exhibits exceptional chemical stability and resistance to oxidation and nitration and provide excellent anti-corrosion properties that prevent corrosive wear in cylinders.

Its balanced sulfated ash level reduces valve surface deposits and provides exceptional valve seat and face protection and reduces the wear and deposit formation in the critical valve guides of highly loaded turbocharged four-cycle engines.

APPLICATIONS / BENEFITS

- Reduces engine wear and extends engine life
- Excellent protection under high temperature operating conditions
- Low ash Formulation and improves spark low ash Formulation plug performance
- Outstanding detergency and dispersancy properties

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE Viscosity Grade	SAE J 300	SAE 40
Specific Gravity @ 15 °C	ASTM D 4052	0.883
Flash Point, °C	ASTM D 92	225
Pour Point , °C	ASTM D 97	-15
Kinematic Viscosity @40°C	ASTM D 445	133
@100°C	ASTM D 445	14.19
Viscosity Index	ASTM D 2270	104
Sulphated Ash Content (%wt)	ASTM D 874	0.51
Color	ASTM D 1500	2.5

MEETS THE REQUIREMENTS OF

- API CF