

UNITED ROCK DRILL OIL

United Rock Drill Oils are a blend of highly refined base oils and special additives which produce a superior lubricant for air powered equipment. The naturally high viscosity index provides optimum lubrication for both low start-up temperatures and high operational temperatures. Extreme pressure additives prevent wear and withstand the high loads commonly encountered in rock drills, jackhammers and other pneumatic equipment.

United Rock Drill Oils contain tackiness agents that permit them to tenaciously adhere to cylinder walls and other lubricated parts. They are also fortified with extreme pressure additives that protect rock drills against wear caused by load shocks.

United Rock Drill Oils are specially developed for use in all types of pneumatic equipment. They are recommended for rock drills, jackhammers, paving breakers, pile drivers, air tools and other pneumatic equipment.

APPLICATIONS / BENEFITS

- Excellent adhesion.
- Excellent dispersancy properties.
- Washout resistant.
- Protect against rust and corrosion.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS			
ISO Viscosity Grade		100	150	320	380
Specific Gravity @ 15 °C	ASTM D 4052	0.888	0.896	0.892	0.893
Flash Point, °C	ASTM D 92	244	252	252	258
Pour Point, °C	ASTM D 97	-9	-9	-6	-6
Kinematic Viscosity @40°C	ASTM D 445	102	146	318	372
@100°C	ASTM D 445	11.6	14.7	24.4	27.1
Viscosity Index	ASTM D 2270	101	100	98	98
Color	ASTM D 1500	<1.5	<2.5	<3.0	<3.5
Timken OK Load, (ibs)				75	75
4 Ball EP, Weld Point (kg)				254	258
4 Ball EP, LWI (kg)				48	48