

UNITED UNIMAR TBN 12

United Unimar TBN 12 lubricant is specially formulated engine oil for lubricating medium-speed and high-speed auxiliary shipboard machineries on board ships. United Unimar TBN 12 is specifically suitable for lubricating gear transmissions, turbo chargers as well as oil lubricated stern tubes.

United Unimar TBN 12 lubricant contains balanced additive composition used in conjunction with highly refined base oils to produce a product which imparts useful performance characteristics such as high load carrying capacity, good detergency and dispersancy properties, excellent rust and corrosion protection for all engine parts and strong alkalinity reserve to neutralize acids formed from the combustion of distillate fuels.

United Unimar TBN 12 is compatible with all major auxiliary engine marine lubricants and can be used for all stationary shipboard auxiliary equipment.

APPLICATIONS / BENEFITS

- High load carrying capacity.
- Rust and oxidation protection.
- Outstanding anti-oxidation properties.
- Compatible with other competitive lubricants.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS		
UNIMAR		312	412	512
SAE Viscosity Grade	SAE J 300	30	40	50
Specific Gravity @ 15 °C	ASTM D 4052	0.896	0.902	0.904
Flash Point, °C	ASTM D 92	230	240	250
Pour Point , °C	ASTM D 97	-9	-9	-9
Kinematic Viscosity @40°C	ASTM D 445	110.1	149.7	204.7
@100°C	ASTM D 445	12.06	14.82	18.0
Viscosity Index	ASTM D 2270	98	98	96
TBN, (mgKOH/g)	ASTM D 2896	12	12	12
Color	ASTM D 1500	<4.5	<4.5	<4.5