

UNITED TURBO XD 9000 S

United Turbo XD 9000 S is formulated using a robust additive package and selected base stocks to deliver real performance in today's heavy-duty diesel engines, especially those fitted with modern features like Super-charger, Turbo-charger and multi-valves drive trains.

United Turbo XD 9000 S is a proven choice with the transportation industry in Asian region. It minimizes high temperature carbon deposits, which is by far the most concerned issue for today's heavily loaded modern diesel engines. The reduced carbon build-up means less rings wear and cylinder bore polishing resulting in much reduced diesel consumption, less ring breakage and piston skirt scuffing. Its high ability to neutralize acidic by-products from the diesel combustion ensures minimum corrosion of the engine parts throughout the lengthy oil drain interval.

APPLICATIONS / BENEFITS

- Minimizes oil consumption.
- Protects against ring and cylinder wear.
- Keeps piston clean.
- Neutralizes acids from high sulfur fuel.
- Maintains efficient fuel consumption.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS	
SAE Viscosity Grade	SAE J 300	15W40*	15W50
Specific Gravity @ 15 °C	ASTM D 4052	0.877	0.881
Flash Point, °C	ASTM D 92	228	228
Pour Point , °C	ASTM D 97	-33	-33
Kinematic Viscosity @40°C	ASTM D 445	113.7	142.2
	@100°C	ASTM D 445	14.8
Viscosity Index	ASTM D 2270	134	142
TBN, (mgKOH/g)	ASTM D 2896	8.2	8.2
Color	ASTM D 1500	<3.0	<3.0

MEETS THE REQUIREMENTS OF

- API CH4/SJ
- Cummins CES20076
- ACEA E5-02
- Mercedes-Benz 228.1 / 228.3
- MAN M3275
- MAN 270 / 271
- Mack Cat 1 / Cat 2
- VOLVO VDS-2

* Please note performance is SAE grade specified.