

UNITED POWER XTG 9

United Power XTG-9 is formulated with the most advanced additive components for its class, protecting engines from the stress of cold starts as well as short trip driving. It provides high temperature protection in all grades, exceeding the toughest standards against thermal breakdown.

APPLICATIONS / BENEFITS

- Formulated for stop and go driving.
- Protects against rust and corrosion.
- Exceeds the highest U.S. standards for automotive engine wear protection.
- Protects engines under severe driving conditions.
- Eliminates the need for extra oil additives.

TYPICAL CHARACTERISTICS

| TEST DESCRIPTION | METHOD | TYPICAL RESULTS | | | |
|---------------------------|-------------|-----------------|-------|-------|-------|
| SAE Viscosity Grade | SAE J 300 | 10W40 | 15W40 | 15W50 | 20W50 |
| Specific Gravity @ 15 °C | ASTM D 4052 | 0.876 | 0.886 | 0.885 | 0.892 |
| Flash Point, °C | ASTM D 92 | 210 | 230 | 228 | 238 |
| Pour Point , °C | ASTM D 97 | -27 | -24 | -24 | -18 |
| Kinematic Viscosity @40°C | ASTM D 445 | 95.7 | 110 | 141 | 175 |
| @100°C | ASTM D 445 | 14.5 | 14.6 | 18.0 | 18.8 |
| Viscosity Index | ASTM D 2270 | 157 | 137 | 145 | 121 |
| TBN, (mgKOH/g) | ASTM D 2896 | 6.1 | 6.1 | 6.1 | 6.1 |
| Color | ASTM D 1500 | <3.0 | <3.0 | <3.0 | <3.0 |

MEETS THE REQUIREMENTS OF

- API SJ
- JASO MA